

Q3.076 INDOOR SPECIFICATION

Module		
1	Pixel pitch	3.076mm
2	Pixel Density	105,625 dots/m ²
3	Pixel configuration	1R1G1B
4	LED type	SMD1515
5	Module size	W320 * H160 * T7.4mm (thickness tolerance±0.5mm)
6	Module weight	230g
7	Module resolution	W104*H52 dots
8	Module QTY/ m ²	19.53 pcs/ m ²
9	Min. Viewing Distance	≥3.076m
10	Brightness	≥500 cd/m ²
11	Viewing Angle	H170°±5° ; V170°±5°
12	Driving Mode	1/26 scan constant current
13	Interface	HUB75
14	Input voltage	4.5V-5V
15	Max. Power Consumption	21 W/ Piece
16	Avg. Power Consumption	11W/ Piece
17	Signal Processing Depth	16384
18	Video frame rate	60 frames/s
19	Refresh Rate	≥1920Hz
20	Defective Dots Rate	<0.0001 (LED industry standard: ≤ 0.0003)
22	Brightness Conformity	≥98.5%
24	MTBF	≥10000 hours
25	Lifespan	≥100000 hours
26	Protective function	Over-heat/Over-load /Power-down /Power-leakage /Lightning-protection etc.
27	Operating Temperature	-10°C ~ 40°C
28	Operating Humidity	10-60% no condensation
29	Storage Temperature	-20°C ~ 60°C
30	Storage Humidity	10-60% no condensation
Control system parameter		
1	Color temperature	3000-18000K
2	Brightness level	16 levels, automatic adjustment.
3	Control way	Computer, real-time, off-line, wireless, internet etc.
4	PC Operation	Windows(XP、 Vista)、 Win7、 Win8、 Win10
5	Video Signal	VGA、 DVI、 RF、 S-Video、 RGBHV YUV、 YC、 COMPOSITION,etc.
6	Communication Distance	Cat5 UTP 100 meters, Multimode optical fiber 500 meters, single 15 km.

Note: The specification may subject to change without prior notice.

